

: 2025	:	
	:	

:		:		:	
		:			

:		:	
		:	
:		:	
:		:	

	Internet				
--	----------	--	--	--	--

:					
:					
* :		, вкажіть t°	°	Гаряча, вкажіть t°	°

\*

	( ) *	**	**	**	( )**	( . )**	***
1							
2							
3							
4							
5							
6							
7							

\*

7,

\*\*

:

\*\*\*

:

:			
:			:
:			?
:			?

--


















							N.	
	115	230	/ *					
	Easy	Pro	Liftronic Air	PN	PN Flex	Linear	:	
( Easy)	80	125	160	240	320	:		
:							:	
**	2500	3000	3500	4000	4500	:		
***	( )							
(mm)					:			
( Easy or Linear)					:			
	RAL 6018		( RAL):					
:								

\* : 400V ±10% 50Hz (3PH+N+PE), 400V ±10% 50Hz (3PH+PE), 460V ±10% 60Hz (3PH+PE)

\*\*

\*\*\*

250

						
						
	: 125	250	: STD	(Ixtur)		
+						
						
( ORBITAL POS.1 POS.2 TILTING )			90°	180°	270°	( ): °
			90°	180°	270°	( ): °
( X Y )	X		90°	180°	270°	( ): °
			90°	180°	270°	( ): °
	Y		90°	180°	270°	( ): °
			90°	180°	270°	( ): °
						
	125	250	500	750	:	
	RAL 1018		( RAL):			
:						

